

IN THE CLAIMS:

Please amend the claims as indicated below:

1. (Previously Presented) A method for processing multimedia data in a User  
 5 Datagram Protocol layer of a wireless receiver conforming to an Internet Protocol standard, said  
 method comprising the steps of:  
     receiving payload error information with said multimedia data from a Radio Link  
 Protocol (RLP) layer; and  
     forwarding said payload error information with said multimedia data to a higher layer.
- 10 2. (Previously Presented) The method of claim 1, wherein said payload error  
 information comprises a set of logical transmission unit error indicators associated with each packet.
3. (Original) The method of claim 2, wherein said error indicators point to a  
 starting and ending location of erroneous data.
4. (Previously Presented) The method of claim 1, further comprising the step of  
 15 performing a packet header cyclic redundancy check.
5. (Currently Amended) The method of claim 4, further comprising the step of  
 forwarding said error indicator, logical transmission unit size and a packet payload to ~~the~~ a FEC  
 decoder if said packet header is valid.
6. (Currently Amended) The method of claim 4, further comprising the step of  
 20 forwarding said error indicator and a packet payload to ~~the~~ a FEC decoder if said packet header is  
 valid.
7. (Previously Presented) The method of claim 1, further comprising the step of  
 processing said payload error information to identify an erasure within each packet.

8. (Previously Presented) The method of claim 1, wherein said multimedia data has been encoded using Maximal Distance Separable codes.

9. (Previously Presented) The method of claim 8, wherein said Maximal Distance Separable codes are Reed-Solomon codes.

5 10. (Previously Presented) The method of claim 8, wherein said Maximal Distance Separable codes are applied to a number,  $k$ , of information packets comprised of  $X$  data units, and wherein up to  $X$  codewords are formed of length  $n$  using one data unit from each of said  $k$  information packets.

10 11. (Previously Presented) The method of claim 8, wherein said Maximal Distance Separable codes are applied to a number,  $k$ , of information packets comprised of  $X$  data units, and wherein up to  $X/L$  codewords of length  $nL$  are formed using  $L$  data units from each of said  $k$  information packets.

15 12. (Previously Presented) The method of claim 8, wherein a first set of said Maximal Distance Separable codes are applied to each of said information packets comprised of  $X$  data units to create  $k$  information packets comprised of  $X'$  data units, and a second set of said MDS codes are applied to each of said information packets comprised of  $X'$  data units, and wherein up to  $X'$  codewords are formed using one data unit from each of said  $k$  information packets.

13. (Previously Presented) The method of claim 1, wherein said payload error information includes a reformatted packet including frame error information from a lower layer.

20 14. (Currently Amended) The method of claim 13, further comprising the step of forwarding said reformatted packet to ~~the~~ a FEC decoder if a cyclic redundancy check on a packet header is valid.

15. (Previously Presented) The method of claim 1, wherein said UDP layer further specifies additional packet handling procedures in accordance with a complete User Datagram Protocol.

5 16. (Previously Presented) A method for receiving multimedia data in a wireless packet network comprising the steps of:  
processing said multimedia data to determine if said multimedia data is properly received; and  
forwarding payload error information with said multimedia data to a higher layer.

10 17. (Previously Presented) The method of claim 16, wherein said payload error information comprises a set of logical transmission unit error indicators associated with each packet.

18. (Original) The method of claim 17, wherein said error indicators point to a starting and ending location of erroneous data.

19. (Previously Presented) The method of claim 16, further comprising the step of performing a packet header cyclic redundancy check.

15 20. (Previously Presented) The method of claim 16, wherein said multimedia data has been encoded using Maximal Distance Separable codes.

21. (Previously Presented) The method of claim 16, wherein said payload error information includes a reformatted packet including frame error information from a lower layer.

20 22. (Currently Amended) The method of claim 21, further comprising the step of forwarding said reformatted packet to an FEC decoder if a cyclic redundancy check on a packet header is valid.

23. (Previously Presented) The method of claim 16, wherein said UDP layer further specifies additional packet handling procedures in accordance with a complete User Datagram Protocol.

24. (Previously Presented) A system for processing multimedia data in a User Datagram Protocol layer of a wireless receiver conforming to an Internet Protocol standard, said system comprising:

a memory for storing computer readable code; and

a processor operatively coupled to said memory, said processor configured to:

receive payload error information with said multimedia data from a Radio Link

Protocol layer; and

forward said payload error information with said multimedia data to a higher layer.

25. (Previously Presented) The system of claim 24, wherein said payload error information comprises a set of logical transmission unit error indicators associated with each packet.

26. (Original) The system of claim 25, wherein said error indicators point to a starting and ending location of erroneous data.

27. (Previously Presented) The system of claim 24, wherein said processor is further configured to perform a packet header cyclic redundancy check.

28. (Currently Amended) The system of claim 25 ~~27~~, wherein said processor is further configured to forward said logical transmission unit error indicators, logical transmission unit size and a packet payload to ~~the~~ a FEC decoder if said packet header is valid.

29. (Currently Amended) The system of claim 25 ~~27~~, wherein said processor is further configured to forward said logical transmission unit error indicators and a packet payload to ~~the~~ a FEC decoder if said packet header is valid.

30. (Previously Presented) The system of claim 24, wherein said processor is further configured to process said payload error information to identify an erasure within each packet.

31. (Previously Presented) The system of claim 24, wherein said multimedia data  
5 has been encoded using Maximal Distance Separable codes.

32. (Previously Presented) The system of claim 31, wherein said Maximal Distance Separable codes are Reed-Solomon codes.

33. (Previously Presented) The system of claim 31, wherein said Maximal Distance Separable codes are applied to a number,  $k$ , of information packets comprised of  $X$  data  
10 units, and wherein up to  $X$  code words are formed of length  $n$  using one data unit from each of said  $k$  information packets.

34. (Previously Presented) The system of claim 31, wherein said Maximal Distance Separable codes are applied to a number,  $k$ , of information packets comprised of  $X$  data units, and wherein up to  $X/L$  code words of length  $nL$  are formed using  $L$  data units from each of  
15 said  $k$  information packets.

35. (Previously Presented) The system of claim 31, wherein a first set of said Maximal Distance Separable codes are applied to each of said information packets comprised of  $X$  data units to create  $k$  information packets comprised of  $X'$  data units, and a second set of said MDS codes are applied to of said information packets comprised of  $X'$  data units, and wherein up to  $X'$   
20 code words are formed using one data unit from each of said  $k$  information packets.

36. (Previously Presented) The system of claim 24, wherein said payload error information includes a reformatted packet including frame error information from a lower layer.

37. (Currently Amended) The system of claim 36, wherein said processor is further configured to forward said reformatted packet to ~~the~~ a FEC decoder if a cyclic redundancy

check on a packet header is valid.

38. (Previously Presented) A system for receiving multimedia data in a wireless packet network comprising:

a memory for storing computer readable code; and

5 a processor operatively coupled to said memory, said processor configured to:  
process said multimedia data to determine if said multimedia data is properly received; and

forward payload error information with said multimedia data to a higher layer.

39. (Previously Presented) The system of claim 38, wherein said payload error  
10 information comprises a set of logical transmission unit error indicators associated with each packet.

40. (Original) The system of claim 39, wherein said error indicators point to a starting and ending location of erroneous data.

41. (Previously Presented) The system of claim 38, wherein said processor is further configured to perform a packet header cyclic redundancy check.

15 42. (Previously Presented) The system of claim 38, wherein said multimedia data has been encoded using Maximal Distance Separable codes.

43. (Previously Presented) The system of claim 38, wherein said payload error information includes a reformatted packet including frame error information from a lower layer.

20 44. (Currently Amended) The system of claim 43, wherein said processor is further configured to forward said reformatted packet to an FEC decoder if a cyclic redundancy check on a packet header is valid.

45. (Withdrawn) A method for transmitting a multimedia packet from a wireless packet network to a wired network conforming to the Internet Protocol (IP), said multimedia packets

encoded using a forward error correction (FEC) coding technique, said method comprising the steps of:

embedding frame error information in said multimedia packet;  
forwarding said multimedia packet to a receiver on said wired network; and  
discarding a multimedia packet having an unrecoverable frame error.

46. (Withdrawn) The method of claim 45, wherein said forward error correction (FEC) coding technique employs Maximal Distance Separable (MDS) codes that are applied to a number,  $k$ , of information packets comprised of  $X$  data units, and wherein up to  $X$  codewords are formed of length  $n$  using one data unit from each of said  $k$  information packets.

47. (Withdrawn) The method of claim 45, wherein said forward error correction (FEC) coding technique employs Maximal Distance Separable (MDS) codes that are applied to a number,  $k$ , of information packets comprised of  $X$  data units, and wherein up to  $X/L$  codewords of length  $nL$  are formed using  $L$  data units from each of said  $k$  information packets.

48. (Withdrawn) The method of claim 45, wherein said forward error correction (FEC) coding technique employs Maximal Distance Separable (MDS) codes that are applied to each of said information packets comprised of  $X$  data units to create  $k$  information packets comprised of  $X'$  data units, and a second set of said MDS codes are applied to of said information packets comprised of  $X'$  data units, and wherein up to  $X'$  codewords are formed using one data unit from each of said  $k$  information packets.

49. (Withdrawn) A method for transmitting a multimedia packet from a wireless packet network to a wired network conforming to the Internet Protocol (IP), said multimedia packets encoded using a forward error correction (FEC) coding technique, said method comprising the steps of:

decoding said multimedia packet using frame error information;  
forwarding said multimedia packet to a receiver on said wired network; and  
discarding a multimedia packet having an unrecoverable frame error.

50. (Withdrawn) The method of claim 49, wherein said forward error correction (FEC) coding technique employs Maximal Distance Separable (MDS) codes that are applied to a number,  $k$ , of information packets comprised of  $X$  data units, and wherein up to  $X$  codewords are formed of length  $n$  using one data unit from each of said  $k$  information packets.

5 51. (Withdrawn) The method of claim 49, wherein said forward error correction (FEC) coding technique employs Maximal Distance Separable (MDS) codes that are applied to a number,  $k$ , of information packets comprised of  $X$  data units, and wherein up to  $X/L$  codewords of length  $nL$  are formed using  $L$  data units from each of said  $k$  information packets.

10 52. (Withdrawn) The method of claim 49, wherein said forward error correction (FEC) coding technique employs Maximal Distance Separable (MDS) codes that are applied to each of said information packets comprised of  $X$  data units to create  $k$  information packets comprised of  $X'$  data units, and a second set of said MDS codes are applied to of said information packets comprised of  $X'$  data units, and wherein up to  $X'$  codewords are formed using one data unit from each of said  $k$  information packets.

15 53. (Withdrawn) A system for transmitting a multimedia packet from a wireless packet network to a wired network conforming to the Internet Protocol (IP), said multimedia packets encoded using a forward error correction (FEC) coding technique, comprising:

a memory for storing computer readable code; and  
 a processor operatively coupled to said memory, said processor configured to:  
 20 embed frame error information in said multimedia packet;  
 forward said multimedia packet to a receiver on said wired network; and  
 discard a multimedia packet having an unrecoverable frame error.

25 54. (Withdrawn) A system for transmitting a multimedia packet from a wireless packet network to a wired network conforming to the Internet Protocol (IP), said multimedia packets encoded using a forward error correction (FEC) coding technique, comprising:

a memory for storing computer readable code; and  
 a processor operatively coupled to said memory, said processor configured to:



decode said multimedia packet using frame error information;  
forward said multimedia packet to a receiver on said wired network; and  
discard a multimedia packet having an unrecoverable frame error.